

1/3 AND 1/2 HP CAST IRON

Submersible Sewage Pumps



WATER SYSTEMS



MODELS 30TC, 50TC

PUMPS
2-in. SOLIDS

NON-CLOGGING

VORTEX IMPELLER

1 YEAR LIMITED WARRANTY

100% FACTORY TESTED

FEATURES AND BENEFITS

- Rugged oil filled, 115V, 60Hz motor
- Thermal overload protects against overheating
- Epoxy coated, cast iron motor housing dissipates heat to ensure long life
- 2" discharge with 2" solids pumping capacity
- Bottom suction inlet with vortex impeller
- Waterproof power cord with grounded plug
- Ceramic and carbon seal for reliable service and extended life
- Temperature Rating: 130°F. (54°C.)

PERFORMANCE

DISCHARGE HEIGHT ABOVE PUMPING LEVEL (LIFT)

	MODEL	HP	AMPS	0 ft.	5 ft.	10 ft.	15 ft.	20 ft.
GALLONS PER MINUTE	30TC	1/3	8.4	80	76	54	15	-
	50TC	1/2	9.5	110	100	86	69	46

1/3 HP CAST IRON

STAR WATER SYSTEMS

Submersible Sewage Pump

- Bottom inlet with vortex impeller
- 2-in discharge passes 2-in solids

80 GPM

NON-CLOGGING VORTEX IMPELLER

PUMPS 2-IN SOLIDS

100% FACTORY TESTED

PERFORMANCE

DISCHARGE HEIGHT ABOVE PUMPING LEVEL (LIFT)	0 ft.	5 ft.	10 ft.	15 ft.	20 ft.
GALLONS PER MINUTE	80	76	54	15	-
LITERS PER MINUTE	302.8	287.7	204.4	56.8	-

1 YEAR LIMITED WARRANTY **115 V**

starwatersystems.com
1-800-742-5044

UPC# 054757095871

1/2 HP CAST IRON

STAR WATER SYSTEMS

Submersible Sewage Pump

- Bottom inlet with vortex impeller
- 2-in discharge passes 2-in solids

110 GPM

NON-CLOGGING VORTEX IMPELLER

PUMPS 2-IN SOLIDS

100% FACTORY TESTED

PERFORMANCE

DISCHARGE HEIGHT ABOVE PUMPING LEVEL (LIFT)	0 ft.	5 ft.	10 ft.	15 ft.	20 ft.
GALLONS PER MINUTE	110	100	86	69	46
LITERS PER MINUTE	416.4	378.5	325.6	261.2	174.1

1 YEAR LIMITED WARRANTY **115 V**

starwatersystems.com
1-800-742-5044

UPC# 054757081041



starwatersystems.com
Toll Free Help Line
1-800-742-5044

SW1582 B