1/3 & 1/2 HP CAST IRON

Column Sump Pumps



FEATURES AND BENEFITS

- · Cast iron base for stability and long life
- · Open type non-clogging multi-vane impeller
- Thermal overload protection keeps motor from overheating
- · Easily adjustable on/off float and rod type switch
- · Top suction strainer filters out debris
- Operates in 130°F water continuously; 150°F intermittently
- Fits into 12" diameter pit



MODELS 3CDH, 5CDH















LIMITED WASSASTY	5 V				
PERFORMANCE / DISCHARGE HEIGHT ABOV ALTURA DE DESCARGA PO	E PUMPINI IR ENCIMA	G LEVEL (LIF	DE DOMBEO		
CALL CASE DED ANDLESS	O ft.	S ft.	10 ft.	15 ft.	20 ft.
GALLONS PER MINUTE LITERS PER MINUTE	0 ft. 65 246,1	5 ft. 59 223,3	10 ft. 51 193,1	15 ft. 38 143,8	20 ft. 17 64,4
	65 246,1	223,3	51	38	17 64,

3CDH	UPC# 05475700085
5CDH	UPC# 054757035129



PERFORMANCE

DISCHARGE HEIGHT ABOVE PUMPING LEVEL (LIFT)

	MODEL	HP	AMPS	0 ft.	5 ft.	10 ft.	15 ft.	20 ft.
GALLONS PER MINUTE	3CDH	1/3	4.0	58	52	41	12	-
	5CDH	1/2	7.3	65	59	51	38	17